

Universal tents



- Immediately ready to use
- Extensive standard features
- Useable area 12 m² to 40 m² (130 to 430 sq. ft.)
- 20 m² (216 sq. ft.) set up in just 1 minute



www.vetter.de/vetter_emergency/en/Rescue+Products/Pneumatic+tents+and+showers/Universal+tents.html

Your pneumatic tent for all kinds of operations.

Vetter universal tents were developed especially for fire brigades. The tents are designed to need especially little time and personnel for transport, setup and takedown.

Benefit from these features of our tents:

- self-erecting support frame
- low weight,
- small folded size
- ease of use

With our pneumatic tents, you can quickly set up protective space for colleagues or injured persons. Use the velcro fasteners to connect tents quickly and easily to other tents or directly with containers.

Vetter universal tents are suited to a wide variety of uses such as living quarters for large-scale operations, triage facilities, or decontamination measures. For the latter, you can add Vetter shower units to all our tents.

Your pneumatic tent for quick operations:

- Only 2 people needed for setup, ready for use in less than three minutes
- Flexible, mobile and easy to use
- Long time of use independent of electricity
- One-piece system in a single package - no loose parts

For optimum performance in the field, Vetter tents are equipped with extensive features - even in the basic version.

Standard components

All universal tents include as standard components:

- Inflatable tent frame with tensioning ropes
- Detachable tent cover with separate entry awnings (partly or completely rollable)
- Detachable tent floor
- Attachment loops in tent interior, e.g. for lamps
- 1 door at each front side
- Sufficient number of windows

The PZ 30 and PZ 40 universal tents are equipped with two air chambers for faster inflation. Each tent includes an accessory bag with hammer, pegs and repair material. All of the equipment is delivered in a handy package with carrying handles.

Tent colours



The Vetter standard colours

You want another colour?

No problem, just call us on: +49 (0)2252 / 3008-60

Emergency Pneumatics

Technical data

- Working pressure: 0.5 bar (7.25 psi)
- Test pressure: 0.65 bar (9.4 psi)

| Product | Art. no. | Setup time, approx. sec / sec | Ext. dimensions (L x W x H) m / ft. | Int. dimensions (L x W x H) m / ft. | Air requirement, at working pressure litres / cu.ft. | Folded size (L x W x H) cm / inch | Weight, approx. kg / lbs | Connectable with Product / Product | Win Quar Que |
|---------|------------|----------------------------------|---|---|--|---|-----------------------------|--|--------------------|
| PZ 12 | 1520002901 | 40 40 | 3,7 x 3,86 x 2,58 11,8 x 12,4 x 8,3 | 3,7 x 3,5 x 2,4 11,8 x 11,2 x 7,7 | 1632 57,6 | 110 x 85 x 40 43 x 33 x 16 | 55 121 | PZ 12 PZ 12 | |
| PZ 17 | 1520000401 | 50 50 | 4,9 x 3,86 x 2,48 15,7 x 12,4 x 7,9 | 4,9 x 3,5 x 2,3 15,7 x 11,2 x 7,4 | 2025 71,5 | 110 x 85 x 60 43 x 33 x 24 | 65 143 | PZ 17 / PZ 20 Decon PZ 17 / PZ 20 Decon | |
| PZ 20 | 1520004701 | 55 55 | 5 x 4,36 x 2,48 16 x 14 x 7,9 | 5 x 4 x 2,3 16 x 12,8 x 7,4 | 2332 82,3 | 110 x 85 x 60 43 x 33 x 24 | 75 165 | PZ 20 PZ 20 | |
| PZ 25 | 1520008901 | 120 120 | 5 x 5,36 x 2,58 16 x 17,2 x 8,3 | 5 x 5 x 2,4 16 x 16 x 7,7 | 2568 90,7 | 110 x 85 x 60 43 x 33 x 24 | 85 187 | PZ 25 PZ 25 | |
| PZ 30 | 1520009402 | 130 130 | 6 x 5,5 x 3,1 19,2 x 17,6 x 9,9 | 6 x 5,14 x 2,9 19,2 x 16,4 x 9,3 | 2866 101,2 | 110 x 85 x 60 43 x 33 x 24 | 104 229 | PZ 30 / PZ 40 / PZ 40 3 L PZ 30 / PZ 40 / PZ 40 3 L | |
| PZ 40 | 1520010602 | 150 150 | 8 x 5,5 x 3,1 25,6 x 17,6 x 9,9 | 8 x 5,14 x 2,9 25,6 x 16,4 x 9,3 | 4060 143,3 | 110 x 85 x 85 43 x 33 x 33 | 117 258 | PZ 30 / PZ 40 / PZ 40 3 L PZ 30 / PZ 40 / PZ 40 3 L | |

Accessories

- Inflation with cylinder
- Inflation with blower
- Deflation
- Equipment
- Lighting
- Climate control
- Water supply



In operation...

- Operation centre
- Weatherproof changing tent
- Crew or mess tent for large- scale operations
- Triage facility



Good reasons...

- Multifunction inflation connection for use with compressed air cylinder or blower
- Remains operational for several days without additional air
- Patented securing net in roof area optionally available



Guaranteed quality:

- Individually tested (with inspection seal)
- Integrated safety valve prevents overinflation
- High- quality, durable support frame
- Mould- and flame- resistant PU- cover material (DIN 4102 B1)

Please contact us directly should you have any further questions concerning this product.

Sales
Phone.: +49 (0) 22 52 / 30 08-0
Fax: +49 (0) 22 52 / 30 08-590
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
